

**LEDTreads** floor lighting systems are manufactured by Tube Lighting Products with the latest LED technology. **LEDTreads** are comprised of heavy PVC tracking with **ModuLEDs** inserted at spacing's per your specifications. **ModuLEDs** consist of a polycarbonate housing, replaceable LED circuit board, and polycarbonate lens cover. They delineate pathways and articulate elevation changes by creating highly visible margins. **LEDTreads** also use less power than traditional filament sources.

**EXTRUSIONS** - Durable UL-approved, non-slip, high grip, black, flexible PVC. See LEDTreads Extrusion specification sheet for dimensions.

**SURFACE MOUNT PRINTED CIRCUIT BOARDS** - 0805 package size LED (4 per board), rated at up to 100,000 hours, and resistors.

**CIRCUIT BOARD COLORS & WATTAGE** - Amber, yellow, red, and green (nominal 0.25 watts/board). Blue and white (nominal 0.5 watts/board). Conformal coated.

**ModuLEDs HOUSING & LENS COVER** - Polycarbonate.

**TERMINALS** - Tin-plated.

**WIRE** - 18 AWG stranded.

**TRANSFORMER** - 12 volt, Class 2.

**ADHESIVE** - Solvent base resin.

**LISTING** - U.L. listed.



## ORDERING INFORMATION

1) Series: LED2

2) Extrusions:

CCE Carpet-to-Carpet Extrusion  
CFE Carpet-to-Floor Extrusion  
CWE Carpet-to-Wall Extrusion  
CCBE Carpet-to-Carpet Bullnose Extrusion  
FFE Floor-to-Floor Extrusion  
FWE Floor-to-Wall Extrusion  
FFBE Floor-to-Floor Bullnose Extrusion

3) **ModuLEDs** Spacing:

9 9" OC  
12 12" OC  
18 18" OC  
Others available-Consult Factory

4) **ModuLEDs** Colors:

A Amber  
B Blue  
G Green  
R Red  
W White  
Y Yellow

5) Number of LEDs in **ModuLEDs**: 4

6) Lens Covers:

C Clear  
P Prismatic  
S Signature

7) Length:

Use feet and inches.

For example: an order of LEDTreads with a Carpet-to-Carpet transition, 12" OC spacing, amber lights, 4 LEDs per ModuLEDs, clear lens covers, having a length of 5 feet and 2 inches; the catalog number would read, **LED2-CCE-12-A-4-C/5'2"**

