

WATTAGE - 20 watts to 96 watts available.

INPUT VOLTAGE - 120VAC to 277VAC available.

OUTPUT VOLTAGE - 12VDC and 24VDC available.

PROTECTION - Short circuit / Over current / Over voltage

CASE - 20 gauge CRS powdercoat and KO's on both ends.

WARRANTY - 2 years from date of purchase.

LISTINGS - U.L. listed.



Constant voltage LED drivers.



Output VDC	Watts	Input VAC	Electronic Non-Dimming	Electronic 0-10 Dimming	Dimensions LxWxH	DRIVER
12	20	110-230	✓		9.5" x 2.2" x 1.5"	DSH-1114-1220
12	35	110-230	✓		9.5" x 2.2" x 1.5"	DSH-1114-1235
12	60	110-230	✓		12.25" x 2.2" x 1.5"	DSH-1115-1260
12	60	110-277		✓	12.25" x 2.2" x 1.5"	DSH-1115-1260-DIM
24	20	110-230	✓		9.5" x 2.2" x 1.5"	DSH-1114-2420
24	35	110-230	✓		9.5" x 2.2" x 1.5"	DSH-1114-2435
24	60	110-230	✓		12.25" x 2.2" x 1.5"	DSH-1115-2460
24	96	110-277	✓		12.25" x 2.2" x 1.5"	DSH-1115-2496
24	96	110-277		✓	12.25" x 2.2" x 1.5"	DSH-1115-2496-DIM