

These 12 volt fully dimmable magnetic power supplies meet or exceed all UL Standards 2108 and 1838, CUL, ANSI/UL, CSA requirements.

OUTPUT VOLTAGE - 12VDC, CLASS 2

PROTECTION - Standard with secondary protection. (See chart below)

DIMMABLE - Lutron Maestro dimmer MRF2-6ND

CASE - Suitable for indoor or outdoor locations.
20 gauge steel powdercoat *NEMA 3R* case.

KNOCKOUTS - Two 7/8" diameter knockouts on bottom of case, used for conduit fittings.

WARRANTY - 3 years after date of purchase.

LISTINGS - E.T.L. Listed.

Made in the U.S.A.



14.25"L x 8.5"W x 5"D

Output VDC	Watts	Input VAC	Breakers	Frequency	Dimensions LxWxH	Weight	DRIVER
12	180	120	3x5A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR180-12V-MAG
12	180	277	3x5A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR180-12V-MAG-277
12	240	120	4x5A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR240-12V-MAG
12	240	277	4x5A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR240-12V-MAG-277
12	300	120	5x5A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR300-12V-MAG
12	300	277	5x5A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR300-12V-MAG-277