

These 24 volt fully dimmable magnetic power supplies meet or exceed all UL Standards 2108 and 1838, CUL, ANSI/UL, CSA requirements.

**OUTPUT VOLTAGE** - 24VDC, CLASS 2

**PROTECTION** - Standard with secondary protection. (See chart below)

**DIMMABLE** - Lutron Maestro dimmer MRF2-6ND

**CASE** - Suitable for indoor or outdoor locations.  
20 gauge steel powdercoat *NEMA 3R* case.

**KNOCKOUTS** - Two 7/8" diameter knockouts on bottom of case, used for conduit fittings.

**WARRANTY** - 3 years after date of purchase.

**LISTINGS** - E.T.L. Listed.

**Made in the U.S.A.**



14.25"L x 8.5"W x 5"D



Output VDC	Watts	Input VAC	Breakers	Frequency	Dimensions LxWxH	Weight	DRIVER
24	192	120	2x4A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR192-24V-MAG
24	192	277	2x4A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR192-24V-MAG-277
24	288	120	3x96VA	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR288-24V-MAG
24	288	277	3x96VA	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR288-24V-MAG-277