

These 24 volt fully dimmable magnetic power supplies meet or exceed all UL Standards 2108 and 1838, CUL, ANSI/UL, CSA requirements.

OUTPUT VOLTAGE - 24VDC, CLASS 2

PROTECTION - Standard with secondary protection. (See chart below)

DIMMABLE - Lutron Maestro dimmer MRF2-6ND

CASE - Suitable for indoor or outdoor locations.
20 gauge steel powdercoat *NEMA 3R* case.

KNOCKOUTS - Two 7/8" diameter knockouts on bottom of case, used for conduit fittings.

WARRANTY - 3 years after date of purchase.

LISTINGS - E.T.L. Listed.

Made in the U.S.A.



Output VDC	Watts	Input VAC	Breakers	Frequency	Dimensions LxWxH	Weight	DRIVER
24	24	120	1x1A	60 Hz	8.5" x 3.625" x 2.25"	3.5 lbs	DSH-DR24-24V-MAG
24	24	277	1x1A	60 Hz	8.5" x 3.625" x 2.25"	3.5 lbs	DSH-DR24-24V-MAG-277
24	60	120	1x2.5A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR60-24V-MAG
24	60	277	1x2.5A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR60-24V-MAG-277
24	96	120	1x4A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR96-24V-MAG
24	96	277	1x4A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR96-24V-MAG-277