

BPS-137 incandescent **RopeLight** is a great indoor/outdoor option for any application. Taking minutes for installation, this fully flexible **RopeLight** does not require a transformer, but simply line voltage at 120V. Available in 150ft reel only.

SPACING - Bulb spacing at 1"

VOLTAGE - Line voltage 120V

WATTAGE - 6 Watts per foot.

TUBE DIAMETER - 0.5" in diameter.

LOCATION - Applicable indoor or outdoor.
 Specified as waterproof and flame-retardant.

MAXIMUM LENGTH - Maximum length per roll is 150 feet.


CUT LENGTH - Available to cut every 24" inches.

DIMMING - Dimmable with standard dimmers.

LIFE HOURS - 25,000 lamp life hours.

ACCESSORIES - Power Cords, Splice Connectors & End Cap available.
 Mounting channels (see specs below) and clips available.

LISTING - U.L. Listed. UL void if BPS-137 is cut.



MOUNTING TRACK SPECIFICATION

This Mounting Channel is a PVC channel used specifically for **LED ROPELIGHT** applications.

MATERIAL - PolyVinyl Chloride (PVC)

LENGTH - Mounting PVC channel available in 3 ft. lengths.

MOUNTING - Channel can be mounted using screws, double-coated tape, or adhesive.

ORDERING INFORMATION

CATALOG #	DESCRIPTION	WATTS / FT	VOLTS	LENGTH
BPS-137-120V-CL	Clear White	6	120	150ft / Reel
BPS-137-120V-BL	Blue	6	120	150ft / Reel
BPS-137-120V-AM	Amber	6	120	150ft / Reel
BPS-137-120V-RD	Red	6	120	150ft / Reel
BPS-137-120V-GN	Green	6	120	150ft / Reel
BPS-137-120V-YL	Yellow	6	120	150ft / Reel