

**SPACING** - 1" on center.

**VOLTAGE** - 120V.

**WATTAGE** - 0.80 watts/ft.

**TUBE DIAMETER** - 0.5" diameter for PVC cable.

**REEL LENGTH** - 150 ft./reel

**LIFE HOURS** - 100,000 hours of life.

**COLORS** - Several colors offered: Clear White, Warm White, Blue, Green, Red, and Yellow.

**DIMMING** - Dimmable with most electronic low voltage and LED/CFL Dimmers. Minimum loads may apply.

**CUT LENGTH** - See Ordering Information below.

**CUSTOM CUTS** - Contact TLP for information.

**ACCESSORIES** - Power Cords, Splice Connectors & End Cap available. Mounting channels (see specs below) and clips available.

**LISTING** - U.L. Listed for wet location. UL void if BPS-281 is cut.

**TEMPERATURE RATING** - 50 - 105°C.

**VOLTAGE & CUT LENGTHS** - 120V - **36"** for White, Warm White, Blue and Green. **54"** for Red and Yellow.


#### **MOUNTING TRACK SPECIFICATION**

This Mounting Channel is a PVC channel used specifically for **LED ROPELIGHT** applications.

**MATERIAL** - PolyVinyl Chloride (PVC)

**LENGTH** - Mounting PVC channel available in 3 ft. lengths.

**MOUNTING** - Channel can be mounted using screws, double-coated tape, or adhesive.



### ORDERING INFORMATION

CATALOG #	DESCRIPTION	WATTS / FT	VOLTS	CUT LENGTH	LENGTH
BPS-281-120V-CW	Cool White	.8	120	36in	150ft / Reel
BPS-281-120V-WW	Warm White	.8	120	36in	150ft / Reel
BPS-281-120V-BL	Blue	.8	120	36in	150ft / Reel
BPS-281-120V-GR	Green	.8	120	36in	150ft / Reel
BPS-281-120V-RD	Red	.8	120	60in	150ft / Reel
BPS-281-120V-YL	Yellow	.8	120	60in	150ft / Reel