

**WATTAGE** - 20 watts to 96 watts available.

**INPUT VOLTAGE** - 120VAC to 277VAC available.

**OUTPUT VOLTAGE** - 12VDC and 24VDC available.

**PROTECTION** - Short circuit / Over current / Over voltage

**CASE** - 20 gauge CRS powdercoat and KO's on both ends.

**WARRANTY** - 2 years from date of purchase.

**LISTINGS** - U.L. listed.

Constant voltage LED drivers.



Output VDC	Watts	Input VAC	Electronic Non-Dimming	Electronic 0-10 Dimming	Electronic ELV Dimming	Dimensions LxWxH	DRIVER
12	20	110-230	✓			9.5" x 2.2" x 1.5"	DSH-1114-1220
12	35	110-230	✓			9.5" x 2.2" x 1.5"	DSH-1114-1235
12	60	110-230	✓			12.25" x 2.2" x 1.5"	DSH-1115-1260
12	60	110-277		✓		12.25" x 2.2" x 1.5"	DSH-1115-1260-DIM
12	60	120			✓	8.2" x 2" x 1.75"	DSH-1116-1260-DIM
12	60	277			✓	8.2" x 2" x 1.75"	DSH-1116-1260-DIM
24	20	110-230	✓			9.5" x 2.2" x 1.5"	DSH-1114-2420
24	35	110-230	✓			9.5" x 2.2" x 1.5"	DSH-1114-2435
24	60	110-230	✓			12.25" x 2.2" x 1.5"	DSH-1115-2460
24	60	120			✓	8.2" x 2" x 1.75"	DSH-1116-2460-DIM
24	60	277			✓	8.2" x 2" x 1.75"	DSH-1116-2460-DIM
24	96	110-277	✓			12.25" x 2.2" x 1.5"	DSH-1115-2496
24	96	110-277		✓		12.25" x 2.2" x 1.5"	DSH-1115-2496-DIM
24	96	120			✓	9.25" x 3.375" x 2"	DSH-1117-2496-DIM
24	96	277			✓	9.25" x 3.375" x 2"	DSH-1117-2496-DIM