

STRANDS are flexible, bright, dimmable, energy efficient LED lighting systems designed to give the creative mind a creative edge. Ideal to use in cove lighting, bar and counter accents, under cabinet task lighting, toe kick accents, refrigerated deli or beverage cases, displays cases, boats, RVs, windows, tradeshow booths, signage, step/walkway lighting, and theatre seating.

SPOOL DIMENSIONS - (W)0.490" x (H)0.196" x (L) 32.8 ft. (10m)

MAXIMUM RUN - 32.8 feet (10M)

WATTAGE - 1.46 watts/ft.

VOLTAGE - 24VDC

LAMPS - LED SMD 3528, 600 LED's per 10m spool, spaced at 0.75" on center. CRI 90+

FIELD CUTTABLE - Every 4 inches.

BEAM ANGLE - 120 degrees.

LUMEN OUTPUT - 80 lumens/ft.

COLORS - White (2400K), White (2700K), White (3100K), White (4000K) and White (6000K).

COLORS (SPECIAL ORDER) - Red, Green, Blue, Amber.

LIFE HOURS - 60,000 hours.

ELECTRICAL - Flexible circuit board ribbon.

MOUNTING OPTIONS - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

WARRANTY - 3 years from date of purchase.

LISTING -  Listed (E166352 IFDR) (E 348777),  approved.



Polymer encased for IP65 applications.

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSHWL-24V-W24	DSHWL-24V-W24	White (2400K)
DSHWL-24V-W27	DSHWL-24V-W27	White (2700K)
DSHWL-24V-W31	DSHWL-24V-W31	White (3100K)
DSHWL-24V-W40	DSHWL-24V-W40	White (4000K)
DSHWL-24V-W60	DSHWL-24V-W60	White (6000K)
DSHWL-24V-RD	DSHWL-24V-RD	Red (SPECIAL ORDER)
DSHWL-24V-GN	DSHWL-24V-GN	Green (SPECIAL ORDER)
DSHWL-24V-BL	DSHWL-24V-BL	Blue (SPECIAL ORDER)
DSHWL-24V-AM	DSHWL-24V-AM	Amber (SPECIAL ORDER)