

BPS-307 are Stringer-Globes, made of shatterproof polycarbonate, injection molded for excellent clarity and a seamless appearance. Each globe is fitted with an o-ring to ensure a snug fit and weatherproof seal.

SOCKETS - Permanently fixed to each cable and sealed with silicone. Each socket is wired to the cable in parallel so individual lamp failures do not effect operation of others. Black (BK) or White (WH).

GLOBE SIZE - Large globe 3.36" x 2.26" or small globe 1.77" x 1.75". For smaller globe add SM to part number: Ex: for Clear use (CLSM)

LED LAMPS - LED lamps are 24 volts (see chart below).

LAMP SPACING - 12", 18", 24" or 36".

GLOBE COLORS - Polycarbonate Clear (CL), Frosted (FR), Red (RD), Blue (BL), Green (GN), or Amber (AM).

CABLE - Highly flexible cable contains AWG 12 stranded and plated conductor. Black (BK) or White (WH).

MOUNTING OPTIONS - Globe Up (GU) Mounting Straps and Globe Down (GD) Adaptor to hang globe (wire rope 1/8" - 3/16" recommended and supplied by others)

LISTING - ETL listed for wet locations.



Globe Down



Globe Up

LAMP#	WATTS	LUMENS	COLOR	LIFE HOURS
LEDWW	0.48	15	2500K	50,000
LEDCW	0.48	20	5500K	50,000
LEDINC	1.8	40	2400K	50,000
LEDBL	0.48	1.5	BLUE	50,000
LEDGN	0.48	4.5	GREEN	50,000
LEDOR	0.48	2.5	ORANGE	50,000
LEDPU	0.48	3.5	PURPLE	50,000
LEDRD	0.48	2.5	RED	50,000

Note: Incandescent 12V and 24V lamps available. Please contact factory for more info.

ORDERING INFORMATION EXAMPLE

PRODUCT	SPACING	LAMP	WIRE	GLOBE	MOUNTING OPTION	LENGTH
BPS-307	24	LEDWW	BK	FR	GD	Length