

## Fluorescent TFL 8700 Specifications

TFL8700 are T8, side mounted, single lamp fixtures with integral ballast.

WATTAGE - Wattage combinations ranging from 17 to 40W

**CONSTRUCTION** All fixtures are constructed of 20 gauge steel.


**COLOR** All fixtures are powder coated, in house, high gloss White. Special paint colors can be accomodated.

**VOLTAGE** All fixtures are standard Universal 120-277

<u>UL</u> - All fixtures carry UL and C-UL listings for dry and damp locations.

**SPECIALTY BALLAST** Many T8 fixtures are available with emergency, dimming or universal ballasts. Contact factory for details.

**CUSTOM** - Should custom requirements be necessary, please contact your local rep or call us at 888-554-8823. Our engineers and design team are eager to accommodate your special requests.



## ORDERING INFORMATION



Catalog Number	Description	Lamps	Length	Dimmable
TFL-8700-UNV-117-T8	Low profile, side mount T8 strip, integral ballast	1 - 17W T8	24"	YES
TFL-8700-UNV-125-T8	Low profile, side mount T8 strip, integral ballast	1 - 25W T8	36"	YES
TFL-8700-UNV-132-T8	Low profile, side mount T8 strip, integral ballast	1 - 32W T8	48"	YES
TFL-8700-UNV-140-T8	Low profile, side mount T8 strip, integral ballast	1 - 40W T8	60"	YES