

SPOOL DIMENSIONS - (W) 0.31" x (H) 0.1" x (L) 32.8 ft. (10m)

MAXIMUM RUN - 27 feet

WATTAGE - 2.88 watts/ft.

VOLTAGE - 24VDC

LAMPS - LED SMD 3528, 600 LED's per 10M spool.
Spaced at 0.625" on center. CRI 90+

FIELD CUTTABLE - Every 2 inches.

BEAM ANGLE - 120 degrees.

LUMEN OUTPUT - 200 lumens/ft.

COLOR - White (2700K, 3000K, 4000K, 6000K).



Colors (Special Order) - White 2400K, Red, Green, Blue, Amber.

LIFE HOURS - 60,000 hours.

ELECTRICAL - Flexible circuit board ribbon. Additional aluminium heat sink may be required.

MOUNTING OPTIONS - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

WARRANTY - 5 years from date of purchase.

CRI - 90+ **LISTINGS** -  Listed (E166352 IFDR) (E 348777),  approved.



ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSH-1369-24V-W24	DSH-1369-24V--W24	White (2400K) (SPECIAL ORDER)
DSH-1369-24V-W27	DSH-1369-24V--W27	White (2700K)
DSH-1369-24V-W31	DSH-1369-24V--W31	White (3100K)
DSH-1369-24V-W40	DSH-1369-24V--W40	White (4000K)
DSH-1369-24V-W60	DSH-1369-24V--W60	White (6000K)
DSH-1369-24V-RD	DSH-1369-24V--RD	Red (SPECIAL ORDER)
DSH-1369-24V-GN	DSH-1369-24V--GN	Green (SPECIAL ORDER)
DSH-1369-24V-BL	DSH-1369-24V--BL	Blue (SPECIAL ORDER)
DSH-1369-24V-AM	DSH-1369-24V--AM	Amber (SPECIAL ORDER)