

**TAPE DIMENSIONS** - (W) 0.476" x (H) 0.084" x (L) 16.4 ft. (5m)

**MAXIMUM RUN** - 32.8 feet (10m)

**WATTAGE** - 2.30 watts/ft.

**VOLTAGE** - 24 VDC

**LAMPS** - LED SMD 5050, 300 LED's per 5m spool.  
Spaced at 1.35" on center.

**FIELD CUTTABLE** - Every 4 inches.

**BEAM ANGLE** - 120 degrees..

**COLOR** - RGB color changing with 3100K White.


**LIFE HOURS** - 50,000 hours

**ELECTRICAL** - Flexible circuit board ribbon

**MOUNTING OPTIONS** - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

**WARRANTY** - 5 years from date of purchase.

**LISTING** -  Listed (E166352 IFDR) (E 348777),  approved.



Polymer encased for IP65 applications.  
IP68 non-submersible available on special order.

## ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR	LED QTY / SPOOL	BEAM ANGLE
DSH-HO-24V-RGBW	DSH-HO-24V-RGBW	Color changing with White.	300	120°