

TAPE DIMENSIONS - (W) 0.31" x (H) 0.05". With pre-applied 3M adhesive

MAXIMUM RUN - 27'

WATTAGE - 3.0 watts/ft

VOLTAGE - 24VDC (See LED Driver spec sheets)

LAMPS - COB, 512 LED per meter, CRI 90+, IP65

FIELD CUTTABLE - Every 2.5 inches.

BEAM ANGLE - 180 degrees.

LUMEN OUTPUT - 300 Lumens/ft.

COLOR - White (2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6000K).

Colors - Red, Green, Blue, Amber.

LIFE HOURS - 50,000 hours.

ELECTRICAL - Flexible chip on board (COB) ribbon. Additional aluminium heat sink may be required.

WARRANTY - 5 years from date of purchase.

LISTINGS -  Listed (E166352 IFDR) (E 348777),  approved.  JA8 Compliant



ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSHWL-COB-3.0-24V-W24	DSHWL-COB-3.0-24V-W24	2400K (SPECIAL ORDER)
DSHWL-COB-3.0-24V-W27	DSHWL-COB-3.0-24V-W27	2700K
DSHWL-COB-3.0-24V-W30	DSHWL-COB-3.0-24V-W30	3100K
DSHWL-COB-3.0-24V-W35	DSHWL-COB-3.0-24V-W35	3500K
DSHWL-COB-3.0-24V-W40	DSHWL-COB-3.0-24V-W40	4000K
DSHWL-COB-3.0-24V-W50	DSHWL-COB-3.0-24V-W50	5000K (SPECIAL ORDER)
DSHWL-COB-3.0-24V-W60	DSHWL-COB-3.0-24V-W60	6000K (SPECIAL ORDER)
DSHWL-COB-24V-RD	DSHWL-COB-24V-RD	Red (SPECIAL ORDER)
DSHWL-COB-24V-GN	DSHWL-COB-24V-GN	Green (SPECIAL ORDER)
DSHWL-COB-24V-BL	DSHWL-COB-24V-BL	Blue (SPECIAL ORDER)
DSHWL-COB-24V-AM	DSHWL-COB-24V-AM	Amber (SPECIAL ORDER)