

TAPE DIMENSIONS - (W) 0.31" x (H) 0.1". With pre-applied 3M adhesive

MAXIMUM RUN - 27 feet

WATTAGE - 2.9 watts/ft.

VOLTAGE - 24VDC (See LED Driver spec sheets)

LAMPS - LED SMD 2824, 120 LED's per meter. Spaced at 0.375" on center. CRI 90+, IP20

FIELD CUTTABLE - Every 3 inches.

BEAM ANGLE - 120 degrees.

LUMEN OUTPUT - 338 lumens/ft.

COLOR - White (2400K, 2700K, 3100K, 3500K, 4000K, 5000K, 6000K).

Colors - Red, Green, Blue, Amber.


LIFE HOURS - 60,000 hours.

ELECTRICAL - Flexible circuit board ribbon. Additional aluminium heat sink may be required.

MOUNTING OPTIONS - See Strands Extrusions specifications sheet

WARRANTY - 5 years from date of purchase.

LISTINGS -  Listed (E166352 IFDR) (E 348777),  approved,  JA8 Compliant



ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSH-3.1-24V-W24	DSH-3.1-24V-W24	White (2400K) (SPECIAL ORDER)
DSH-3.1-24V-W27	DSH-3.1-24V-W27	White (2700K)
DSH-3.1-24V-W31	DSH-3.1-24V-W31	White (3100K)
DSH-3.1-24V-W35	DSH-3.1-24V-W35	White (3500K)
DSH-3.1-24V-W40	DSH-3.1-24V-W40	White (4000K)
DSH-3.1-24V-W50	DSH-3.1-24V-W50	White (5000K) (SPECIAL ORDER)
DSH-3.1-24V-W60	DSH-3.1-24V-W60	White (6000K) (SPECIAL ORDER)
DSH-3.1-24V-RD	DSH-3.1-24V-RD	Red (SPECIAL ORDER)
DSH-3.1-24V-GN	DSH-3.1-24V-GN	Green (SPECIAL ORDER)
DSH-3.1-24V-BL	DSH-3.1-24V-BL	Blue (SPECIAL ORDER)
DSH-3.1-24V-BL	DSH-3.1-24V-BL	Amber (SPECIAL ORDER)

REV. 05/11/26