

**TAPE DIMENSIONS** - (W) 0.275" x (H) 0.053". With pre-applied 3M adhesive

**MAXIMUM RUN** - 32.8 feet

**WATTAGE** - 2.2 watts/ft.

**VOLTAGE** - 24VDC (See LED Driver spec sheets)

**LAMPS** - LED SMD 2835, 600 LED's per 10m spool, spaced at 1.50" on center. CRI 90+, IP65

**FIELD CUTTABLE** - Every 4 inches

**BEAM ANGLE** - 120 degrees.

**LUMEN OUTPUT** - 246 lumens/ft.

**COLOR** - White (2400K, 2700K, 3100K, 3500K, 4000K, 5000K, 6000K).

Colors - Red, Green, Blue, Amber.

**LIFE HOURS** - 60,000 hours.

**ELECTRICAL** - Flexible circuit board ribbon.

**MOUNTING OPTIONS** - See Strands Extrusions specifications sheet

**WARRANTY** - 5 years from date of purchase.

**LISTINGS** -  Listed (E166352 IFDR) (E 348777),  approved,  JA8 Compliant



## ORDERING INFORMATION

| CATALOG #       | DESCRIPTION     | LED COLOR                     |
|-----------------|-----------------|-------------------------------|
| DSHWL-S-24V-W24 | DSHWL-S-24V-W24 | White (2400K) (SPECIAL ORDER) |
| DSHWL-S-24V-W27 | DSHWL-S-24V-W27 | White (2700K)                 |
| DSHWL-S-24V-W31 | DSHWL-S-24V-W31 | White (3100K)                 |
| DSHWL-S-24V-W35 | DSHWL-S-24V-W35 | White (3500K)                 |
| DSHWL-S-24V-W40 | DSHWL-S-24V-W40 | White (4000K) (SPECIAL ORDER) |
| DSHWL-S-24V-W50 | DSHWL-S-24V-W50 | White (5000K) (SPECIAL ORDER) |
| DSHWL-S-24V-W60 | DSHWL-S-24V-W60 | White (6000K) (SPECIAL ORDER) |
| DSHWL-S-24V-RD  | DSHWL-S-24V-RD  | Red (SPECIAL ORDER)           |
| DSHWL-S-24V-GN  | DSHWL-S-24V-GN  | Green (SPECIAL ORDER)         |
| DSHWL-S-24V-BL  | DSHWL-S-24V-BL  | Blue (SPECIAL ORDER)          |
| DSHWL-S-24V-AM  | DSHWL-S-24V-AM  | Amber (SPECIAL ORDER)         |

REV. 04/16/26