Tube Lighting Products

DSH-1118 Series
UL LISTED ELECTRONIC DRIVERS
Specifications

The DSH-1118 Series are a constant voltage class 2 electronic 24 volt, universal dimming driver. It supports ELV, 0-10 dimming, as well as triac dimmers that supports forward and reverse phase dimming.

NEMA 3R enclosure available.

STANDARD ENCLOSURE IP67.

WATTAGE - 40 watts, 60 watts, 96 watts, 192 watts, 200 watts, 288 watts, 300 watts.

INPUT VOLTAGE - 120VAC to 277VAC.

OUTPUT VOLTAGE - 24VDC.

PROTECTION - Short circuit / Over current / Over voltage

CASE - 20 gauge CRS powdercoat and KO's on both ends.

WARRANTY - 5 years from date of purchase.

LISTINGS - U.L. listed.

- Exceeds California Title 24 Requirements, AAA rating
- High performance LED driver
- Universal Input voltage: 120-277V AC
- Universal dimming with ELV, Triac & 0-I0V dimmers 100-0%
- Flicker free dimming
- Aluminum casing for optimal heat dissipation
- Isolated output power per NEC and UL safety requirements
- UL & ETL recognized/ listed, meets UL 8750, 1310 requirements
- Auto-reset; short circuit, overload and thermal protection
- Efficient, High power factor> 0.90

INPUT VAC	OUTPUT VDC	WATTS	0-10 Dim	ELV Dim	Triac Dim	Class	Dimensions (LxWxH)	Part Number
120-277	24	40	Y	Y	Y	2	8" x 2.75" x 1.63"	DSH-1118-2440-DIM
120-277	24	40	Y	Y	Y	2	11.03" x 4.06" x 2.21"	DSH-1118-2440-DIM-NEMA3R
120-277	24	60	Y	Y	Y	2	9.19" x 3.37" x 1.93"	DSH-1118-2460-DIM
120-277	24	60	Y	Y	Y	2	11.03" x 4.06" x 2.21"	DSH-1118-2460-DIM-NEMA3R
120-277	24	96	Y	Y	Y	2	9.19" x 3.37" x 1.93"	DSH-1118-2496-DIM
120-277	24	96	Y	Y	Y	2	11.03" x 4.06" x 2.21"	DSH-1118-2496-DIM-NEMA3R
120-277	24	192	Y	Y	Y	2	10.08" x 3.05" x 1.79"	DSH-1118-24192-DIM
120-277	24	200	Y	Y	Y	1	10.08" x 3.05" x 1.79"	DSH-1118-24200-DIM
120-277	24	288	Y	Y	Y	2	10.86" x 3.05" x 1.79"	DSH-1118-24288-DIM
120-277	24	300	Y	Y	Y	1	10.86" x 3.05" x 1.79"	DSH-1118-24300-DIM

REV. 10/12/26

1346 Pioneer Way, El Cajon, CA 92020 | (619) 442-0577 / FAX (619) 442-0578 | www.TubeLightingProducts.com